Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for reducing radio signal interference caused by simultaneously deployed scrambling codes, performing allocation of channelisation codes to channels in a Code Division Multiple Access (CDMA) system, the CDMA system deploying any combination of channels operating in a first Compressed Mode (CPM) type requiring reallocation of channels to a channelisation code with a lower spreading factor and channels according to a second CPM type which do not require a reallocation, the method comprising:

organizing having the channelisation codes-organised in a primary code tree and zero or more secondary code trees, where each of the code trees has zero or more alternative code trees, each code tree having one or more channelisation codes per spreading factor, where the channelisation codes are, according to their position in the code tree, denoted consecutively by a code index with a lowest to a highest value per spreading factor within each code tree; and where the system deploys any combination of channels which may operate in a first Compressed Mode (CPM) type requiring reallocation of channels to a channelisation code with a lower spreading factor, and channels according to a second CPM type, which do not require reallocation, the method comprising:

allocating a channelisation code with a lowest code index out of a group of free channelisation codes for a certain spreading factor to the channel according to the first Compressed Mode type; and

allocating a channelisation code with a highest code index out of the group of free channelisation codes for the certain spreading factor to a channel according to the second Compressed Mode type; and

transmitting radio signals utilizing the allocated channelization codes.

EUS/J/P/08-3073

2. (Previously Presented) The method according to claim 1 wherein a request for allocation of a channelisation code for a channel includes the type of CPM to be deployed.

3. (Original) The method according to claim 1, wherein the group of free channelisation codes for a certain spreading factor comprises channelisation codes from the primary code tree.

4. (Previously Presented) The method according to claim 3, wherein the group of free channelisation codes for a certain spreading factor also comprises channelisation codes from one or more secondary code trees.

5. (Previously Presented) The method according to claim 4, wherein the group of free channelisation codes for a certain spreading factor also comprise channelisation codes from one or more alternative code trees, each of the one or more alternative code trees being related to said primary or the one or more secondary code trees.

- 6. (Previously Presented) The method according to claim 5, wherein selection of a channelisation code from the group of free channelisation codes for a certain spreading factor from the primary code tree has precedence over a channelisation code from each of the one or more alternative code trees, where the one or more alternative code trees are related to the primary code tree.
- 7. (Previously Presented) The method according to claim 6, wherein the selection of a channelisation code from the group of free channelisation codes for a certain spreading factor from the one or more alternative code trees, where the one or more alternative code trees are related to the primary code tree, has precedence over a channelisation code from the secondary code tree.

- 8. (Previously Presented) The method according to claim 5, wherein selection of a channelisation code from the group of free channelisation codes for a certain spreading factor from the secondary code tree, has precedence over a channelisation code from an alternative code tree, where the alternative code tree is related to the secondary code tree.
- 9. (Previously Presented) The method according to claim 3, wherein the group of free channelisation codes do not include channelisation codes that are reserved.
- 10. (Previously Presented) The method according to claim 1 where the reallocation of a channelisation code is limited in time duration.
- 11. (Previously Presented) The method according to claim 1, further comprising the steps of:
- determining the type of CPM of the channel which is to be allocated a channelisation code;
- selecting a channelisation code from the group of free channelisation codes with a lowest code index, hence starting from the left side of the primary code tree for allocating a channelisation code for a channel according to the first Compressed Mode type;
- selecting a channelisation code from the group of free channelisation codes with a highest code index, hence starting from the right side of the primary code tree for allocating a channelisation code for a channel according to the second Compressed Mode type.
- 12. (Previously Presented) The method according to claim 1 wherein allocating a channelisation code to a channel according to a first CPM type comprises the steps of:
- creating a list of candidate channelisation codes in the primary code tree which are free and not reserved;

Appl. No. 10/596,854 Amdt. Dated March 20, 2008 Reply to Office action of December 20, 2007

Attorney Docket No. P16272-US1

EUS/J/P/08-3073

- excluding from the list a candidate channelisation code, having a corresponding

parent code at the associated alternative code tree which is not free:

- selecting and allocating a candidate channelisation code from the list with a

lowest code index, hence from the left side of the code tree, on the primary code tree, if

more than one candidate channelisation code exists in the primary code tree;

- reallocating a channel according to the second Compressed Mode type from

the primary code tree to an alternative code tree if there is no candidate channelisation

code on the list, and allocating the freed channelisation code to the channel according

to the first CPM type;

- allocating a channelisation code from a new secondary code tree if insufficient

free space is created through reallocation of channels according to the second CPM

type.

13. (Previously Presented) The method according to claim 1 wherein allocating a

channelisation code to a channel according to the second CPM type comprises the

steps of:

- creating a list of candidate channelisation codes in the primary (or secondary)

code tree which are free and not reserved;

- selecting and allocating a channelisation code from the list with a highest code

index, hence from the right side of the code tree, on the primary (or secondary) code

tree, if more than one candidate exists in the primary (or secondary) code tree;

- creating a first alternative list, if no candidate channelisation code at the primary

(or secondary) code tree exists, with candidate channelisation codes at a right side

alternative code tree related to the primary (or secondary) code tree, which

channelisation codes must be free and not reserved and with the restriction that the

same channelisation code at the related primary (or secondary) code tree must be used

by a channel according to the second CPM type;

- selecting and allocating the candidate channelisation code with the highest

code index from said first alternative list if more than one candidate channelisation code

exists:

Page 9 of 20

- creating a second alternative list with candidate channelisation codes at a left alternative code tree, which alternative code is related to said primary code tree, if no candidate channelisation code at the right alternative code tree exists, which channelisation codes must be free and not reserved and the same channelisation code at the primary code tree must be used by a channel according to the second CPM type;
- selecting and allocating the candidate channelisation code with the highest code index from said second alternative list if more than one candidate channelisation code exists:
- allocating a channelisation code from a new secondary code tree if no candidate channelisation code at the left alternative code tree exists.
- 14. (Previously Presented) The method according to claim 11, wherein the steps of allocating a channelisation code to a channel according to the second CPM type are executed on the primary code tree or the secondary code tree and

the steps of allocating a channelisation code to a channel according to a first CPM type are executed on the primary code tree or the secondary code tree.

- 15. (Previously Presented) The method according to claim 1 wherein the first CPM type is a Spreading Factor divide by 2 (SF/2) method, and the second CPM type is a Higher level scheduling (HLS) or puncturing method.
- 16. (Previously Presented) The method according to claim 1 wherein the CDMA system is a WCDMA system.
 - 17. 24. (Canceled)
- 25. (Currently Amended) A <u>Code Division Multiple Access (CDMA) system</u> comprising:
 - a base station, the base station comprising:

means for reducing radio signal interference caused by simultaneously deployed scrambling codes, the means for reducing radio signal interference comprising:

means for organizing channelisation codes in a primary code tree
and zero or more secondary code trees, where each of the code trees has zero or more
alternative code trees, each code tree having one or more channelisation codes per
spreading factor, where the channelisation codes are, according to their position in the
code tree, denoted consecutively by a code index with a lowest to a highest value per
spreading factor within each code tree

node for performing allocation of channelisation codes to channels in a Code
Division Multiple Access (CDMA) system having the channelisation codes organised in
a primary code tree and zero or more secondary code trees, where each of the code
trees has zero or more alternative code trees, each code tree having one or more
channelisation codes per spreading factor, where the channelisation codes are,
according to their position in the code tree, denoted consecutively by a code index with
a lowest to a highest value per spreading factor within each code tree, wherin the
CDMA system deploys any combination of channels which may operate in a first
Compressed Mode (CPM) type requiring reallocation of channels to a channelisation
code with a lower spreading factor, and channels according to a second CPM type,
which do not require reallocation, the node comprising:

means for allocating a channelisation code with a lowest code index out of a group of free channelisation codes for a certain spreading factor to the channel according to the first Compressed Mode type; and

means for allocating a channelisation code with a highest code index out of the group of free channelisation codes for the certain spreading factor to a channel according to the second Compressed Mode type; and

means for transmitting radio signals utilizing the allocated channelization codes.

26. (Currently Amended) The <u>system node</u> according to claim <u>25</u> [[1]] wherein a request for allocation of a channelisation code for a channel includes the type of CPM to

be deployed.

27. (Currently Amended) The <u>system node</u> according to claim <u>25</u> [[1]], wherein

the group of free channelisation codes for a certain spreading factor comprises

channelisation codes from the primary code tree.

28. (Currently Amended) The system node according to claim 27, wherein the

group of free channelisation codes for a certain spreading factor also comprises

channelisation codes from one or more secondary code trees.

29. (Currently Amended) The system node according to claim 28 wherein the

group of free channelisation codes for a certain spreading factor also comprise

channelisation codes from one or more alternative code trees, each of the one or more

alternative code trees being related to said primary or the one or more secondary code

trees.

30. (Currently Amended) The system node according to claim 29, wherein a

channelisation code selected from the group of free channelisation codes for a certain

spreading factor from the primary code tree has precedence over a channelisation code

from each of the one or more alternative code trees, where the one or more alternative

code trees are related to the primary code tree.

31. (Currently Amended) The system node according to claim 30, wherein a

channelisation code selected from the group of free channelisation codes for a certain

spreading factor from the one or more alternative code trees, where the one or more

alternative code trees are related to the primary code tree, has precedence over a

channelisation code from the secondary code tree.

Page 12 of 20

- 32. (Currently Amended) The <u>system node</u> according to claim 29, wherein a channelisation code from the group of free channelisation codes for a certain spreading factor selected from the secondary code tree, has precedence over a channelisation code from an alternative code tree, where the alternative code tree is related to the secondary code tree.
- 33. (Currently Amended) The <u>system node</u> according to claim 27, wherein the group of free channelisation codes do not include channelisation codes that are reserved.
- 34. (Currently Amended) The <u>system node</u> according to claim 25, wherein the reallocation of a channelisation code is limited in time duration.
- 35. (Currently Amended) The <u>system node</u> according to claim 25, further comprising means for:
- determining the type of CPM of the channel which is to be allocated a channelisation code;
- selecting a channelisation code from the group of free channelisation codes with a lowest code index, hence starting from the left side of the primary code tree for allocating a channelisation code for a channel according to the first Compressed Mode type;
- selecting a channelisation code from the group of free channelisation codes with a highest code index, hence starting from the right side of the primary code tree for allocating a channelisation code for a channel according to the second Compressed Mode type.
- 36. (Currently Amended) The <u>system node</u> according to claim 25 wherein means for allocating a channelisation code to a channel according to a first CPM type comprises means for:

- creating a list of candidate channelisation codes in the primary code tree which are free and not reserved;
- excluding from the list a candidate channelisation code, having a corresponding parent code at the associated alternative code tree which is not free;
- selecting and allocating a candidate channelisation code from the list with a lowest code index, hence from the left side of the code tree, on the primary code tree, if more than one candidate channelisation code exists in the primary code tree;
- reallocating a channel according to the second Compressed Mode type from the primary code tree to an alternative code tree if there is no candidate channelisation code on the list, and allocating the freed channelisation code to the channel according to the first CPM type;
- allocating a channelisation code from a new secondary code tree if insufficient free space is created through reallocation of channels according to the second CPM type.
- 37. (Currently Amended) The <u>system</u> node according to claim 25 wherein means for allocating a channelisation code to a channel according to the second CPM type comprises means for:
- creating a list of candidate channelisation codes in the primary (or secondary) code tree which are free and not reserved;
- selecting and allocating a channelisation code from the list with a highest code index, hence from the right side of the code tree, on the primary (or secondary) code tree, if more than one candidate exists in the primary (or secondary) code tree;
- creating a first alternative list, if no candidate channelisation code at the primary (or secondary) code tree exists, with candidate channelisation codes at a right side alternative code tree related to the primary (or secondary) code tree, which channelisation codes must be free and not reserved and with the restriction that the same channelisation code at the related primary (or secondary) code tree must be used by a channel according to the second CPM type;

Appl. No. 10/596,854 Amdt. Dated March 20, 2008

Reply to Office action of December 20, 2007

Attorney Docket No. P16272-US1

EUS/J/P/08-3073

- selecting and allocating the candidate channelisation code with the highest

code index from said first alternative list if more than one candidate channelisation code

exists;

- creating a second alternative list with candidate channelisation codes at a left

alternative code tree, which alternative code is related to said primary code tree, if no

candidate channelisation code at the right alternative code tree exists, which

channelisation codes must be free and not reserved and the same channelisation code

at the primary code tree must be used by a channel according to the second CPM type;

- selecting and allocating the candidate channelisation code with the highest

code index from said second alternative list if more than one candidate channelisation

code exists; and

means for allocating a channelisation code from a new secondary code tree if no

candidate channelisation code at the left alternative code tree exists.

38. (Currently Amended) The system node according to claim 35, wherein

the means for allocating a channelisation code to a channel according to the

second CPM type utilize the primary code tree or the secondary code tree and

the means for allocating a channelisation code to a channel according to the first

CPM type utilize the primary code tree or the secondary code tree.

39. ((Currently Amended) The system node according to claim 25 wherein the

first CPM type is a Spreading Factor divide by 2 (SF/2) method, and the second CPM

type is a Higher level scheduling (HLS) or puncturing method.

40. (Currently Amended) The system node according to claim 25 wherein the

CDMA system is a WCDMA system.

Page 15 of 20